



## General Feature

- Absorbent Glass Mat(AGM) technology for efficient gas recombination of up to 99% and freedom from electrolyte maintenance or water adding.
- Not restricted for air transport-complies with IATA/ICAO Special Provision A67.
- UL-recognized component.
- Can be mounted in any orientation.
- Computer designed lead, calcium tin alloy grid for high power density.
- Long service life, float or cyclic applications.
- Maintenance-free operation.
- Low self discharge.



## SPECIFICATION

Nominal voltage	12V
Number of cell	6
Length(mm/inch)	197/7.76
Width(mm/inch)	165/6.5
Height(mm/inch)	170/6.69
Total Height(mm/inch)	170/6.69
Approx. Weight(kg/lbs)	13.5/29.8











## Battery Construction

Component	Positive plate	Negative plate	Container	Cover	Safety valve	Terminal	Separator	Electrolyte
Raw material	Lead dioxide	Lead	ABS	ABS	Rubber	Copper	Fiberglass	Sulfuric acid

## Performance Characteristics

Capacity 77°F(25°C)	20 hours rate(2.35A 10.8V)	47Ah
	10 hours rate(4.5A 10.8V)	45Ah
	5 hours rate(7.42A 10.5V)	37.1Ah
	1 hour rate(28A 9.6V)	28Ah
Internal Resistance	Full charged battery 77°F(25°C):8mΩ	
Capacity affected by Temperature (10 hour rate)	104°F(40°C)	102%
	77°F(25°C)	100%
	32°F(10°C)	85%
	5°F(-15°C)	65%
Self-Discharge 68°F(20°C)	Capacity after 3 month storage	90%
	Capacity after 6 month storage	80%
	Capacity after 12 month storage	60%
Max discharge current 77°F(25°C):450A(5S)		
Charge (Constant Voltage)	Float:13.6 to 13.8V/77°F(25°C)	
	Cycle:14.4 to 14.7V/77°F(25°C) Max Current:11.3A	



### Discharge Constant Current (Amperes at 77° F 25 °C)

End Point Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60V	149	100	77.8	45.7	28.0	11.8	7.80	4.62	2.42
1.65V	142	96.5	74.8	43.9	27.5	11.6	7.68	4.60	2.41
1.70V	134	91.5	71.6	42.0	27.0	11.3	7.55	4.58	2.40
1.75V	125	86.0	68.3	40.0	26.4	11.0	7.42	4.55	2.38
1.80V	114	80.0	64.8	37.8	25.7	10.7	7.27	4.50	2.35

(Note)The above characteristics data are average values obtained Within three charge/discharge cycles not the minimum values.

### Discharge Constant Power (watts at 77° F 25 °C)

End Point Volts/Cell	5min	10min	15min	30min	45min	1h	2h	3h	5h
1.60V	263	187	147	98.5	74.5	59.2	33.5	24.5	15.8
1.65V	252	179	142	95.5	72.0	57.4	32.5	23.8	15.4
1.70V	239	170	137	92.0	69.0	55.4	31.4	23.0	14.9
1.75V	224	160	131	88.0	66.0	53.4	20.3	22.2	14.4
1.80V	206	148	124	83.0	62.5	51.2	29.1	21.3	13.8

(Note)The above characteristics data are average values obtained Within three charge/discharge cycles not the minimum values.